


L-3 Communications Tape, Electrical, Silicone Self-Fusing, Standard & Limited Stretch Versions (Supported and Non-Supported)

500°F / 260°C: Meeting A-A-59163 Class 1, Type I Specifications & MIL-I-22444

Also meets MIL-I-46852 & Many Other OEM Specifications

Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing within minutes, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets A-A-59163, MIL-I-46852 and MIL-I-22444 specifications.
- Standard roll length is 36 feet / 12 Yards / 10.9 Metres; other lengths available. Standard color is Black.
- CofC available.
- Cage Code L8347.

L-3 Communications Tape, Electrical, Silicone Self-Fusing, Standard non-supported Meets MIL-I-46852 & A-A-59163 Specifications: Class 1, Type I

Part Number	Tape Width Inches / mm	Thickness inches / mm	Type / Profile	Single Roll Price Per Roll
T-SR-40014362-000	1/2 / 13	0.020 / 0.5	I / Rectangular	\$ 29.37
T-SR-40014362-001	3/4 / 19	0.020 / 0.5	I / Rectangular	\$ 31.96
T-SR-40014362-002	1 / 25	0.020 / 0.5	I / Rectangular	\$ 34.71
T-SR-40014362-003	1.25 / 32	0.020 / 0.5	I / Rectangular	\$ 41.77

L-3 Communications Tape, Electrical, Silicone Self-Fusing, Limited Stretch supported Meets MIL-I-22444 Specifications

T-SR-7186328-000	1/2 / 13	0.020 / 0.5	I / Rectangular	\$ 56.33
T-SR-7186328-001	1 / 25	0.050 / 1.27	I / Rectangular	\$ 145.01