

## UL 94 V-0 Flamability Standards Silicone Tape

Operating temperature 400°F / 204°C:

**FlameShield™ Silicone Rubber Self Fusing Compression & Stretch Electrical**

**Insulating Tape – Flame Retardant**

**Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant**



- Produced with UL V-0 recognized flame retardant silicone rubber compound.
- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing upon contact, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets A-A-59163 and other proprietary specifications.
- -65°F / -51°C low temperature range.
- CofC available.
- Available in Brown or Black.

**FlameShield™ Flame Resistant High Temperature Silicone Self Fusing  
Compression/Stretch Electrical Insulating Tape  
Meets UL 94 V-0 Flame Test Standards and A-A-59163 Specifications**

Part Number	Tape Width Inches / mm	Thickness inches / mm	Type / Profile
T-SR-UL-16-RXX-10	1 / 25	0.010 / 0.25	I / Rectangular
T-SR-UL-16-RXX-20	1 / 25	0.020 / 0.51	I / Rectangular
T-SR-UL-16-RXX-30	1 / 25	0.030 / 0.76	I / Rectangular
T-SR-UL-16-RXX-40	1 / 25	0.040 / 1.02	I / Rectangular

- Standard roll length is 36 feet / 12 Yards / 10.9 Metres
- For the XX value (color code): BK = Black, BR = Brown