

**Ceramic Fiber Tadpole Tape With Rope or Wire Mesh Core**  
**2000°F / 1093°C CerMax™ TadpoleTape™ Extreme High Temperature Heat Flame Resistant**



Made from our highest temperature ceramic fiber inconel wire inserted materials, this is a soft and resilient gasket material for effective sealing on metal flanges and where limited bolting force is available – and where doors and other closures rest on the bulb of the tape.

Available by-the-foot and standard 50 and 100 feet rolls.

Can be used at 2000°F / 1093°C continuously.

TadpoleTape™ Very High Temperature & Heat Resistant CerMax™ Ceramic		
Rope Core	Stainless Steel or Inconel 600 Mesh Core	Over All Width in / mm
Part Number	Part Number	
TT-C-RC-M025-16-X	TT-C-MC-M025-16-X-Z	1.00 / 25
TT-C-RC-M032-20-X	TT-C-MC-M032-20-X-Z	1.25 / 32
TT-C-RC-M038-24-X	TT-C-MC-M038-24-X-Z	1.50 / 38
TT-C-RC-M044-28-X	TT-C-MC-M044-28-X-Z	1.75 / 44
TT-C-RC-M051-32-X	TT-C-MC-M051-32-X-Z	2.00 / 51
TT-C-RC-M063-40-X	TT-C-MC-M063-40-X-Z	2.50 / 63
TT-C-RC-M076-48-X	TT-C-MC-M076-48-X-Z	3.00 / 76

For the “X” value: specify either A, B, C, D, or E

“A” = 3/8” / .375” / 7.9mm; “B” = 1/2” / .500” / 13mm; “C” = 5/8” / .625” / 15.8mm; “D” = 3/4” / .750” / 19mm; “E” = 1” / 1.000” / 25mm

For the “Z” value: specify “S” for Stainless Steel or “I” for Inconel

NOTE: 1.0” OAW not available with 5/8, 3/4 or 1” bulb. 1.25” OAW not available with 1” bulb. 1.5” OAW not available with 1” bulb

**OTHER CUSTOM SIZES & SHAPES AVAILABLE – PLEASE INQUIRE**