

Fiberglass Tadpole Tape with Fiberglass Rope or Wire Mesh Bulb Core 1200°F / 648°C TadpoleTape™ Very High Temperature & Heat Resistant



Made from our heavy duty fiberglass fabrics and ropes, and metallic mesh ropes, this is a soft and resilient gasket material for effective sealing on light metal flanges and where limited bolting force is available – and where doors and other closures rest on the bulb.

Available by-the-foot and standard 50 and 100 feet rolls.

A Heat Treated version of this product is available for clean room door sealing – please enquire

Fabricated from high quality type E fiberglass that will not burn and will withstand continuous exposure to temperatures of 1200°F / 648°C. This product resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable.

| TadpoleTape™ Very High Temperature & Heat Resistant Fiberglass | | |
|--|--|---------------------------|
| Rope Core | Stainless Steel or Inconel 600 Mesh Core | Over All Width in / mm |
| Part Number | Part Number | |
| TT-FG-RC-M025-16-X | TT-FG-MC-M025-16-X-Z | 1.00 / 25 |
| TT-FG-RC-M032-20-X | TT-FG-MC-M032-20-X-Z | 1.25 / 32 |
| TT-FG-RC-M038-24-X | TT-FG-MC-M038-24-X-Z | 1.50 / 38 |
| TT-FG-RC-M044-28-X | TT-FG-MC-M044-28-X-Z | 1.75 / 44 |
| TT-FG-RC-M051-32-X | TT-FG-MC-M051-32-X-Z | 2.00 / 51 |
| TT-FG-RC-M063-40-X | TT-FG-MC-M063-40-X-Z | 2.50 / 63 |
| TT-FG-RC-M076-48-X | TT-FG-MC-M076-48-X-Z | 3.00 / 76 |

For the “X” value: specify either A, B, C, D, or E

“A” = 3/8” / .375” / 7.9mm; “B” = 1/2” / .500” / 13mm; “C” = 5/8” / .625” / 15.8mm; “D” = 3/4” / .750” / 19mm; “E” = 1” / 1.000” / 25mm

For the “Z” value: specify “S” for Stainless Steel or “I” for Inconel

NOTE: 1.0” OAW not available with 5/8, 3/4 or 1” bulb. 1.25” OAW not available with 1” bulb. 1.5” OAW not available with 1” bulb

OTHER CUSTOM SIZES & SHAPES AVAILABLE – PLEASE INQUIRE