

Tubing Group

PVDF Kynar® Tubing



Translucent, semi-rigid co-polymer tubing for higher pH chemical applications.

FDA and USP Class VI compatible.

Temperature range -25°F to 250°F (-31°C to 156°C)

Construction: Translucent white Kynar® extruded to tight tolerance.

Standard lengths of 50 and 100 feet.

<p align="center">Tubing Group PVDR Kynar®</p>					
Part Number	ID Size	OD Size	Working Pressure PSI	Weight in lbs/ft	Price/ft
TU-PVDF-KYNAR-0170	0.170	¼"	240	0.03	\$ 4.38
TU-PVDF-KYNAR-02-01	1/8"	1/4"	375	0.04	\$ 4.76
TU-PVDF-KYNAR-03-01	3/16"	5/16"	300	0.04	\$ 6.62
TU-PVDF-KYNAR-04-01	1/4"	3/8"	240	0.06	\$ 8.32
TU-PVDF-KYNAR-05-01	5/16"	0.437	210	0.06	\$ 9.58
TU-PVDF-KYNAR-06-01	3/8"	1/2"	180	0.07	\$ 11.42
TU-PVDF-KYNAR-08-01	1/2"	5/8"	145	0.09	\$ 14.30
TU-PVDF-KYNAR-10-01	5/8"	3/4"	120	0.11	\$ 17.88
TU-PVDF-KYNAR-12-01	3/4"	7/8"	100	0.13	\$ 20.30

Sold in Full Coils Only