

Tubing Group

Viton® Tubing



Exceptional chemical, oil and acid resistance and a wide temperature range.

High quality multi-purpose tubing.

Excellent flexural fatigue characteristics.

Can be used for peristaltic pump applications.

Temperature range -40°F to 400°F (-40°C to 204°C)

Construction: Black, 100% pure Viton rubber. 75 durometer. Also available in 60 durometer for peristaltic pump applications.

Standard length is 50 feet.

Tubing Group				
Viton® Tubing (50 ft coils)				
Part Number	ID Size	OD Size	Weight in lbs	Price
TU-VITON-01-031	1/16"	0.125	0.5	\$ 129.00
TU-VITON-02-01	1/8"	0.250"	1 1/2	\$ 231.00
TU-VITON-03-01	3/16"	0.312"	2	\$ 279.00
TU-VITON-04-01	1/4"	0.375"	2.5	\$ 368.00
TU-VITON-05-01	5/16"	0.437"	3.0	\$ 416.00
TU-VITON-06-01	3/8"	0.500"	4.5	\$ 521.00
TU-VITON-06-02	3/8"	0.625"	7.5	\$ 1177.00
TU-VITON-08-01	1/2"	0.625"	4.5	\$ 726.00
TU-VITON-08-02	1/2"	0.750"	10.0	\$ 1484.00

Sold in Full Coils Only