

Firesleeve with Metallic Zipper Closure - ZipSleeve™

500°F / 260°C Continuous Rating – Higher Temperature for Shorter Periods

High Temperature, Heat, Flame & Fire Resistant Firesleeve

Removable silicone rubber coated fiberglass sleeve with metal zipper provides heavy duty weld splatter & molten splash protection that is removable and retrofit.



This heavy duty silicone rubber coated fibreglass sleeve with high temperature zipper closures protects industrial wire, cable and hose with the benefits of being installed & removed as required.

Typical applications are as robotic welding cable protection, steel mill roll-stand hydraulic hose protection or as a cover in extreme environments where serviceability is required.

The zipper is made from high temperature Nomex® fabric and metal teeth. This is a custom fabrication – please allow 3 to 10 business days from date of order.

The standard maximum length of a zipper is 50 feet / 15 metres. Longer zippers of up to 150 feet / 45 metres are possible, but will incur minimum order quantities. 500°F / 260°C continuous rating with weld splatter / molten metal splash protection.

Also an excellent cold temperature sleeve with flexibility to -76°C for refrigeration and cryogenic applications.

The sleeve has a special flap under the zipper to ensure the full protection of the cable or hose underneath.

Meets 14 CFR 25.869(a)(4); Appendix F, Part 1(b)(7) (60-degree flammability Test).

For aviation and other critical applications, metal clamps secured at regular short intervals can be used to secure the sleeve in place in case of zipper failure due to a concentrated or prolonged heat or flame event.

Custom ZipSleeve™ can also be fabricated with a flap covering the zipper - sewn on one side and with a hook and loop closure on the other side of the flap.

**500°F / 260°C continuous rating with weld splatter / molten metal splash protection.
Higher temperatures for short durations.**

Firesleeve with Metallic Zipper Closure (Continued)
500°F / 260°C Continuous Rating – Higher Temperature for Shorter Periods
High Temperature, Heat, Flame & Fire Resistant Firesleeve



ZipSleeve™ Firesleeve			
Heavy Duty Removable Molten Splash Protection Sleeve			
Nominal ID inches / mm / Dash #			Part Number
1	25	-16	S-FS-ZC-M025-16
1 1/4	32	-20	S-FS-ZC-M032-20
1 1/2	38	-24	S-FS-ZC-M038-24
1 3/4	44	-28	S-FS-ZC-M044-28
2	51	-32	S-FS-ZC-M051-32
2 1/4	57	-36	S-FS-ZC-M057-36
2 1/2	64	-40	S-FS-ZC-M064-40
2 3/4	70	-44	S-FS-ZC-M070-44
3	76	-48	S-FS-ZC-M076-48
3 1/4	83	-52	S-FS-ZC-M083-52
3 1/2	89	-56	S-FS-ZC-M089-56
3 3/4	95	-60	S-FS-ZC-M095-60
4	102	-64	S-FS-ZC-M102-64
4 1/4	108	-68	S-FS-ZC-M108-68
4 1/2	114	-72	S-FS-ZC-M114-72
4 3/4	121	-76	S-FS-ZC-M121-76
5	127	-80	S-FS-ZC-M127-80
5 1/4	133	-84	S-FS-ZC-M133-84
5 1/2	140	-88	S-FS-ZC-M140-88
5 3/4	146	-92	S-FS-ZC-M146-92
6	152	-96	S-FS-ZC-M152-96
6 1/4	159	-100	S-FS-ZC-M159-100
6 1/2	165	-104	S-FS-ZC-M165-104
6 3/4	171	-108	S-FS-ZC-M171-108
7	178	-112	S-FS-ZC-M178-112
7 1/4	184	-116	S-FS-ZC-M184-116
7 1/2	191	-120	S-FS-ZC-M191-120
7 3/4	197	-124	S-FS-ZC-M197-124
8	203	-128	S-FS-ZC-M203-128
8 1/4	210	-132	S-FS-ZC-M210-132
8 1/2	216	-136	S-FS-ZC-M216-136
8 3/4	222	-140	S-FS-ZC-M222-140
9	229	-144	S-FS-ZC-M229-144

This Product is Available By-The-Foot / Metre